

# Direct Plug-In USB Headsets



Order Code  
JPL-402S-USB

Order Code  
JPL-401S-USB

TECHNICAL DATA	
<b>Microphone:</b>	
Directional:	Bi-directional
Impedance:	Max. 2.2K $\Omega$ 1KH(RL=2.2K $\Omega$ )
Sensitivity:	-43 $\pm$ 3dB RL=2.2K $\Omega$ Vs=2.0V (DC)
Frequency Range:	100-10000Hz
Operating Temp:	-25 $^{\circ}$ C~+70 $^{\circ}$ C
Storage Temp:	-40 $^{\circ}$ C~+80 $^{\circ}$ C
<b>Speaker:</b>	
Impedance:	24 $\Omega$ $\pm$ 15% at 0.1 V1000Hz
Sound pressure:	132dB $\pm$ 3dB at 1000HZ
Frequency range:	FO ~20KHZ( $\pm$ 10dB)
	FO: 150Hz $\pm$ 20%
Operating Temp:	-25 $^{\circ}$ C 50 $^{\circ}$ C
Storage Temp:	-25 $^{\circ}$ C 60 $^{\circ}$ C



USB-A



CLOTHING CLIP



## JPL-401S / 402S

Universal 'Plug & Play' USB office and contact centre headset. No software download needed.

### Overview

Features	Single or dual speaker options
	Fitted with headband cushion for maximum all day comfort
	Fitted with 55mm leatherette ear cushions
	Surround Shield™ noise cancelling microphone
	Clear, crisp sound
	In-line control with volume & mute
	Left / right side microphone placement
	'Put and stay' ratchet microphone boom arm
	Overhead, sure-fit fully adjustable headband
	What's included
Headset Weight	Mid-weight Headset, ~ 62g / ~82g
Connection	USB-A
Compatibility	Direct Plug-in
Certifications	CE, RoHS, REACH
Warranty	2 Years repair or replacement warranty
MOQ	Master Shipping Carton: 80
EAN:	JPL-401S-USB: 5060126957997, JPL-402S-USB: 5060126958017
SKU:	JPL-401S-USB: 575-327-001, JPL-402S-USB: 575-327-002

